



AHD 52SERIES

2Megapixel AHD Camera



4IN1SYSTEM

AHD TVI CVI ANALOG SUPPORT





Feature

- 1/2.9" SONY CMOS sensor
- 4-in-1 (AHD/TVI/CVI/CVBS)
- Resolution 1080P, 720P
- Lens 3.6mm.
- IR SMD 17pcs, IR Distance 30-40M
- Day&Night IRCUT, ATW, BLC, FLC, WDR, 3DNR
- OSD cable, UTC, IP66

4IN1SYSTEM

AHD TVI CVI ANALOG SUPPORT

Specification

Model	HA-524B202E
Image Sensor	1/2.9" Sony IMX323 CMOS Progressive Scan
DSP	Fulhan FH8536H (V30H)
Pixels Resolution	1080P, 720P
Video System Output	4-in-1(AHD/TVI/CVI/CVBS)
Min. Illumination	0.1 lux full color
Shutter Speed	1/25s-1/100,000s
Day&Night	EXT, AUTO, COLOR, B/W
Automatic Gain Control	Support AGC
Digital Wide Dynamic Range	Support DWDR
Exposure Mode	Goble, center, BLC, FLC
White Balance	Support ATW, MWB, Gray World,
Digital Noise Reduction	Support 3DNR
Image Adjustment	Support brightness, contrast, sharpness, saturation
S/N	Ratio >58dB.
Signal System	PAL/NTSC
Lens	
Mount Type	M12
Auto Iris	Auto Electric Iris
Focal Length	3.6mm. / F2.0
Focus Mode	Manual
Angle of View	85°
Infrared	
IR LED IR SMD	17 Pcs.
IR Distance	30-40M.
IR Intensive	Support IR Smart
IR CUT	Support
User Interface	
OSD Menu	Support (OSD Cable)
OSD Language	Support
Control Over Coax (COC)	Support COC/UTC
Electrical	
Power	DC Jack 12V.+10%
Power Consumption	IR off 1.4-2W., IR On 5.7-6W.
Environmental	
Operating Temperature	-30°C~+60°C
Storage Temperature	-30°C~+50°C
Working Humidity	10%~90% RH
Lighting Protection	Power 600W for DC jack /video 2KV for BNC
Ingress Protection	IP66
Hardware Interface	
Video Output	BNC x1 (Femail 1.0Vp-p at 75Ω)
Power Input	DC Jack x1 (DC12V)
Machanical	
Case Material	Aluminum Build-in Bracket
Weight	0.38KG
Dimension	181mm x 68mm x 70mm

